



# Oskorp

## Oskorp GoldWrap High performance Building Wrap.

### Highlights

- E2556 Type II weather barrier
- Non-woven construction
- Air barrier
- Water-resistive barrier
- Breathes to allow moisture vapor to escape

Date: 5/28/2025

Revision: 1

### Technical Information

Property	Test Method	Value
Nominal Thickness (in / mils)	-	0.017 / 17
Nominal Width (ft)	-	09 / 10
Tensile Strength (MD / TD) <sup>1</sup> (lb/in)	ASTM D5034	50/40
Water Penetration Resistance (CM H <sub>2</sub> O)	AATCC 127	600
Water Vapor Permeance (Perm)	ASTM E96 (Desiccant Method)	20
Trapezoid Tearing Strength (MD / TD) <sup>1</sup> (lbf)	ASTM D4533	24/20
Water Vapor Transmission Rate g/(m <sup>2</sup> -24hr)	ASTM E96 (Desiccant Method)	170
Air Permeance (L/(s·m <sup>2</sup> )@ 75 Pa) (cfm/ft <sup>2</sup> @1.57 psf)	ASTM E2178	<0.02 <0.004
<b>Fire &amp; Smoke</b> Flame Spread <sup>2</sup> Smoke Developed <sup>2</sup>	ASTM E84	0 (Class A) 75

<sup>1</sup> Machine Direction / Cross Direction.

<sup>2</sup> These numerical flame spread and smoke developed ratings are not intended to reflect hazards presented by this material under actual fire conditions. All applicable building codes must be followed.



# Oskorp

## Description

Oskorp GoldWrap is a non-woven building wrap with a breathable polyolefin coating that performs as both a water-resistant barrier and as an air barrier in accordance with the International Building, Residential and Energy Codes.

It is an excellent secondary weather barrier that helps deflect water and wind-driven rain, yet is designed to breathe to assist trapped moisture vapor to escape, helping walls dry faster.

Oskorp GoldWrap is non-perforated, providing superior resistance against the rain before the siding goes on and against water that seeps through the siding after installation.

Oskorp GoldWrap is UV resistant up to 6 months.

## Compliance

- Intertek CCRR-1018 for IBC, IECC and IRC Compliance;
- DrJ Engineering TER No. 1407-05 (NFPA 285)
- ASTM E2178 – Air Permeance (Air Barrier Materials)
- ASTM E2556, Type II – Standard specification for vapor permeable flexible sheet water-resistant barriers intended for mechanical attachment
- AC 38 – Acceptance Criteria for Water-Resistive Barriers.

## Handling Instruction

When stored outdoors, all products should be protected from exposure to direct sunlight using the original packaging or an opaque, light-colored tarp. Material that has been unwrapped should be covered or rewrapped.

WARNING: This product is combustible. A protective barrier or thermal barrier is required as specified in the appropriate building code. Protect it from exposure to open flame or other

## Health & Safety

Oskorp GoldWrap is made of synthetic materials that are generally recognized as not providing a food source for insects, fungus, mold, or mildew. It should always be properly installed and stored.

*Oskorp Inc. believes the information and recommendations herein to be accurate and reliable. However, since use conditions are not within its control, Oskorp Inc. does not guarantee results from use of such products or other information herein and disclaims all liability from any resulting damage or loss. No warranty, express or implied, is given as to the merchantability, fitness for particular purpose, or otherwise with respect to the products referred to.*